

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the present application:

Listing of Claims:

1. (currently amended) A method for terminating an over-the-air (OTA) programming call comprising the steps of:
 - a network initiating the OTA programming call to a mobile subscriber unit, the OTA programming call comprising an OTA programming session;
 - the mobile subscriber unit receiving the over-the-air programming call;
 - the mobile subscriber unit for detecting an expected termination of the OTA programming call by the network upon the end of the OTA programming session;
 - and
 - the mobile subscriber unit terminating the OTA programming call if the expected termination of the OTA programming call by the network is not detected, wherein the expected termination of the OTA programming call is detected without a prior request from the mobile subscriber unit for an end of session indicator.
2. (original) The method of claim 1, wherein the over-the-air programming session is an over-the-air service provisioning session.
3. (original) The method of claim 1, wherein the over-the-air programming session is an over-the-air service parameter administration session.
4. (previously presented) The method of claim 1, wherein a failure to receive an expected termination of the OTA programming call is a result of a communication error.
5. (previously presented) The method of claim 1, wherein the step of detecting a failure of the network to terminate the OTA programming further comprises detecting

that a time-out period has lapsed without receiving an over-the-air message that the over-the-air session has ended.

6. (previously presented) The method of claim 1, further comprising the step of:
the mobile subscriber unit detecting a condition associated with a failed over-the-air call release.

7. (previously presented) The method of claim 6, wherein the step of detecting a condition associated with the failed over-the-air call release comprises detecting a transition from a digital network to an analog network while engaged in the associated over-the-air programming call.

8. (currently amended) A mobile subscriber unit, comprising:
a processor connected to a wireless communication interface, the processor receiving an over-the-air programming session in an over-the-air call initiated by a network and received via the wireless communication interface:
an end of session detector connected to the processor configured to detect an expected end of session indicator sent by the network, wherein the expected end of session indicator is detected without a prior request from the mobile subscriber unit for an end of session indicator; and
a call terminator coupled to the end session detector, the call terminator configured to terminate the over-the-air call when the end of session detector fails to detect the expected end of session indicator.

9. (previously presented) The mobile subscriber unit of claim 8, wherein the end session indicator is an end of session message.

10. (previously presented) The mobile subscriber unit of claim 8, wherein the end session detector comprises a timer configured to timeout after a time-out period if the expected end of session indicator is not detected.

11. (previously presented) The mobile subscriber unit of claim 8, further comprising a circumstance evaluator configured to detect a condition associated with a failure of the end of session detector to detect the expected end of session indicator.

12. (previously presented) The mobile subscriber unit of claim 11, wherein the circumstance evaluator is configured to detect a transition from a digital network to an analog network while the mobile subscriber unit is engaged in the over-the-air call.

13. (currently amended) A wireless communications system comprising:
a plurality of base stations;
a system server configured to send an over-the-air programming call to a plurality of mobile subscriber units via the plurality of base stations, the system server configured to terminate the over-the-air programming call, the over-the-air programming call comprising an over-the-air programming session and an end of session indicator; and
each mobile subscriber unit of the plurality of mobile subscriber units comprising:
a transceiver circuit configured to receive the over-the-air programming call;
an end of session detector connected to the transceiver circuit and configured to detect the end of session indicator received from the system server, wherein the end of session indicator is received from the server without a prior request from the mobile subscriber unit for an end of session indicator, and
a call terminator connected to the transceiver circuit and the end session detector, the call terminator configured to terminate the over-the-air programming call when the end session detector fails to detect the end of the session indicator.

14. (original) The system of claim 13, wherein the plurality of base stations includes a digital base station.

15. (original) The system of claim 13, wherein the plurality of base stations includes an analog base station.

16. (previously presented) The system of claim 13, wherein the end session indicator is an end of session message sent by the system server.

17. (previously presented) The system of claim 13, wherein the end session detector of the each mobile subscriber unit comprises a timer configured to timeout after a time-out period if the end of session indicator is not received from the system server.

18. (previously presented) The system of claim 13, wherein the each mobile subscriber unit further comprises a circumstance evaluator connected to the transceiver circuit and configured to detect a condition associated with a failure to receive the end of session indicator.

19. (previously presented) The system of claim 18 wherein the plurality of base stations comprises a digital base station and an analog base station, and wherein the circumstance evaluator of the each mobile subscriber unit is configured to detect a transition from a digital network associated with the digital base station to an analog network associated with the analog base station.

20. (previously presented) A method for an over-the-air programming session, comprising:

- a mobile subscriber unit receiving an over-the-air programming call on a communication channel to begin an over-the-air programming session, the over-the-air programming call initiated by a wireless network, the over-the-air programming call comprising an end-of-session indicator;

- the mobile subscriber unit transitioning from a digital network to an analog network while engaged in the over-the-air programming session;

- the mobile subscriber unit determining that the end-of-session indicator has not been received from the wireless network, wherein the determining step of occurs without a prior request for the end-of-session indicator from the mobile subscriber unit; and

the mobile subscriber unit terminating the over-the-air programming call by releasing the communication channel upon the determination that the end-of-session indicator has not been received.

21. (original) The method of claim 20, wherein the over-the-air programming session is an over-the-air service provisioning session.

22. (original) The method of claim 20, wherein the over-the-air programming session is an over-the-air service parameter administration session.

23. (previously presented) The method of claim 20, wherein the end-of-session indicator comprises an over-the-air end of session message received from the wireless network.

24. (previously presented) The method of claim 20, wherein the step of determining that the end-of-session indicator has not been received further comprises detecting that a time-out period has lapsed without receiving an over-the-air end of session message from the wireless network.